



User Manual

VGA to HDMI Video Adapter with USB Audio & Power - Black

Y10A218-B1

Congratulations

Thank you for purchasing this premium Rocstor product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

Features

Upstream:

HDMI - Female



Downstream:

USB-A - Male



• Suppoert Audio & Power

VGA - Male



• Supports common VGA video resolution.

Common VGA Resolution	HDMI	
	800X600	1024X768
	1152X864	1280X600
	1280X720	1280X768
	1280X800	1280X960
	1280X1024	1360X768
	1366X768	1400X1050
	1440X900	1600X900
	1600X1200	1680X1050
	1920X1080	

Features

- Easy to Use: Install in seconds, no need of setting.
- Conversion: It can convert PC's VGA video and USB 2CH audio into complete HDMI.
- Supports 165MHz/1.65Gbps per channel (6.75Gbps all channel) bandwidth.
- Supports 8bit per channel (24bit all channel) deep color.
- Support input resolution up to 1080P

Introduction

This is a premium Rocstor VGA video converter, It converts VGA signal into complete HDMI and allows PC users to enjoy their larger image on the display. The Converter is also along with USB audio that allows you to enjoy high quality sound on HDTV. USB port can supply power to this converter to save an extra power adapter.

Package Contents

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the Packaging:

- 1 x Main Unit
- User Manual

How to Use

Before installation, please make sure all the devices you wish to connect have been turned off.

- 1- Connect the HDMI output of this product to the HDTV which has HDMI input (HDMI Cables are optional).
- 2- Connect the VGA and USB port of this product to computer.
- 3- Power on the computer and TV.
- 4- Set the right resolution of PC to HDTV.

Note: Because the some resolution formats of VGA are not the same with HDTV's, so not all resolutions of VGA can output to HDTV. Please set these resolutions as listed in the Specification as possible.

Specification

Signal Input / Output	
Input Video Signal Input DDC Signal Output Video	0.45-1.1 volts (p-p) 5 volts p-p (TTL) HDMI
Operating Frequency	
Vertical Frequency Range Video Amplifier Bandwidth	50/60Hz 1.65Gpbs/165MHz
Mechanical	
Size(W-H-D) VGA line length USB line length	3.1"x0.47"x2.16" - 80x12x 55 mm 1 ft - 0.3m 3.2 ft - 1m
Warranty	
Limited Warranty	2 Year
Environmental	
Operating Temperature Operating Humidity Storage Temperature Storage Humidity	0°C to + 45°C - (32°F to + 113°F) 10% to 90 % RH (no condensation) -10°C to + 70°C - (14°F to + 158°F) 10% to 90 % RH (no condensation)
Regulatory Approvals	, , , , , , , , , , , , , , , , , , , ,
Certifications	FCC, CE
Power Requirement	
External Power Supply Power consumption (Max) Accessories	NO 1.85W
User Manual	English Version



Host Computer with USB & VGA

Support

Technical support is available to all the registered users of Rocstor products.

Technical Support / RMA

Hours: 9:00 am - 5:00 pm PST Monday to Friday (except holidays) Tell: +1 (818) 727-7000 (National and international)

Fax: +1 (818) 875-0002 Email: support@Rocstor.com





Warranty Information

Warranty Information

This product is backed by a (2)two-year warranty. Rocstor warrants its products against defects in materials and workmanship for the periods noted, following the initial date of purchase. During this period, the products may be returned for repair, or replacement with equivalent products at our discretion. The warranty covers parts and labor costs only. Rocstor does not warrant its products from defects or damages arising from misuse, abuse, alteration, or normal wear and tear.

Limitation of Liability

In no event shall the liability of Rocstorage, Inc. and Rocstor (or their officers, directors, employees or agents) for any damages (whether direct or indirect, special, punitive, incidental, consequential, or otherwise), loss of profits, loss of business, or any pecuniary loss, arising out of or related to the use of the product exceed the actual price paid for the product. Some states do not allow the exclusion or limitation of incidental or consequential damages. If such laws apply, the limitations or exclusions contained in this statement may not apply to you.

⚠ Safety Information:

WARNING: Please follow these safety instructions. Failure to do so may result damages or injury. It is normal that the Rocstor Multi-port Hub adapter becomes very warm during use.

continuous contact with warm surfaces for extended time may cause discomfort or injury. In order to reduce the possibility of overheating or heat-related injuries, always allow needed ventilation around the Rocstor Multi-port Hub adapter and use care when handling it. Avoid instances where your skin is in extended contact with the hub when plugged into the host computer. It is not recommended to sleep with the adapter when plugged into a host computer. Avoid placing the hub adapter under a pillow, blanket, or your body when connected to a host computer. If you have a medical condition that affects your ability to detect heat against the body, extra care should be used. Never use the adapter in locations with water, such as a sink, bathtub, or shower stall. Never connect or disconnect the adapter with wet hands.

©2021 Rocstroge, Inc. All rights reserved. Rocstor is registered trademark of Rocstorage, Inc. Apple®, the Apple logo, Mac®, MacBook®, MacBook Pro®, MacBook Air®, iPad®, iPad Air®, iP registered trademarks of Google, LLC. Microsoft® is registered trademarks of Microsoft corporation. Al other product names and logos mentioned herein may be trademarks of their respective companies. USB Type-C® and USB-C® are registered trademark of USB Implementers Forum. Feature and specification are subject to change without notice. All trademarks and registered trademarks are the property of their respective. All rights reserved.



