



User Manual

Type-C to HDMI/USB-AX2/RJ45 with DP1.4 Alt mode

Y10A304-B1

Congratulations

Thank you for purchasing this premium Rocstor product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

Features

Upstream:

USB Type-C Male (Connect to a host computer)



• Support DP1.4 Alt mode, with bandwidth max 2 lanes 16.2Gbps (8.1Gbps per lane), downward compatible with DP1.2 Alt mode

Note: To get max bandwidth, the host should support DP1.4 Alt mode

Downstream:

HDMI (DP Alt Mode Only)



USB-A X2



- Supports max 4K/60Hz output with
- 18Gbps Bandwidth • Supports 8/10 bit color depth output
- Supports output pixel format RGB / YCbCr4:4:4/ YCbCr4:2:2/ YCbCr4:2:0
- Supports HDR ,HPD
- Supports HDCP 2.2&HDCP1.4

Note: When connecting a DP1.4 Alt mode supported host, the max resolution of HDMI is 4k/60Hz; When connecting a DP1.2 Alt mode supported host, the max resolution of HDMI is 4k/30Hz due to bandwidth limitation

- · Max 5Gbps data transmission per port
- Supports USB 3.0 Specification
- Supports short-circuit, over-current, over-voltage protection

RJ45



- Supports Gigabit Ethernet,10M/100M/1000M
- Supports Wake-On-LAN
- Supports full duplex flow control
- Light indicates the state, no light when no Internet connected, orange light turns on when network connection is established, yellow light flashes when transmitting data

Introduction

Rocstor introduces a Type-C 4-in-1 hub featuring HDMI, USB-A, and Gigabit Ethernet ports, offering an optimal solution for expanding the port options of Type-C/Thunderbolt 3 hosts, especially those with a single Type-C port. With its integrated captive cable that can be conveniently wrapped at the bottom, this hub enhances user experience and convenience. Utilizing the DP1.4 Alt mode supported IC, it enables HDMI video output at a maximum resolution of 4k/60Hz while simultaneously transferring USB 3.1 data at up to 5Gbps. Additionally, the Gigabit Ethernet port ensures super-fast Ethernet connectivity. Compatible with all DP Alt mode supported Type-C hosts, this hub provides versatile compatibility and seamless operation.


Package Contents

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the packaging:

- Main Unit x1
- User Manual

Specification

Input / Output Connector	
Input	USB-C Male x1
Output	HDMI Female x1
	USB-A Female x2
	RJ45 x1
Mechanical	
Weight	g
Size	mm
Warranty	
Limited Warranty	3 Years
Environmental	
Operating Temperature	0°C to 45°C (32°F to 113°F)
Operating Humidity	10% to 90% RH (no condensation)
Storage Temperature	-10°C to 70°C (14°F to 158°F)
Storage Humidity	10% to 90 % RH (no condensation)
Electronic Parameter	
Working Voltage	4.75-5.3V
Working Current	400mA-2700mA
Power Consumption	2W
Regulatory Approvals	
Certifications	FCC, CE
Accessory Adapter	
User Manual	English Version



Support

Technical support is available to all the registered users of Rocstor products.

Technical Support / RMA

Hours: 9:00 am - 5:00 pm PST Monday to Friday (except holidays) Tell: +1 (818) 727-7000 (National and International)

Fax: +1 (818) 875-0002

Email: support@rocstor.com

∧ Safety Information:

WARNING:

Please follow these safety instructions. Failure to do so may result damages or injury. It is normal that the device adapter becomes very warm during use.

Please note that:

Continuous contact with warm surfaces for extended time may cause discomfort or injury. In order to reduce the possibility of overheating or heat-related injuries, always allow needed ventilation around the device and use care when handling it. Avoid instances where your skin is in extended contact with the device when plugged into the host computer. It is not recommended to sleep with the device when plugged into a host computer. Avoid placing the device under a pillow, blanket, or your body when connected to a host computer. If you have a medical condition that affects your ability to detect heat against the body, extra care should be used. Never use the device in locations with water, such as a sink, bathtub, or shower stall. Never connect or disconnect the device with wet hands.





Warranty Information

Warranty Information

This product is backed by a (3) three-year warranty. Rocstor warrants its products against defects in materials and workmanship for the periods noted, following the initial date of purchase. During this period, the products may be returned for repair, or replacement with equivalent products at our discretion. The warranty covers parts and labor costs only. Rocstor does not warrant its products from defects or damages arising from misuse, abuse, alteration, or normal wear and tear.

Limitation of Liability

In no event shall the liability of Rocstor, Inc. and Rocstor (or their officers, directors, employees or agents) for any damages (whether direct or indirect, special, punitive, incidental, consequential, or otherwise), loss of profits, loss of business, or any pecuniary loss, arising out of or related to the use of the product exceed the actual price paid for the product. Some states do not allow the exclusion or limitation of incidental or consequential damages. If such laws apply, the limitations or exclusions contained in this statement may not apply to you.

©2024 Rocstor, Inc. All rights reserved. Rocstor is registered trademark of Rocstor, Inc. Apple®, the Apple logo, Mac®, MacBook®, MacBook Pro®, MacBook Air®, iPad®, iPad Air®, iPad mini®, iPad Air®, iPhone®, MacOS® are registered trademarks of Apple, Inc. Google® and Chromebook™ are $registered\ trademarks\ of\ Google, LLC.\ Microsoft° is\ registered\ trademarks\ of\ Microsoft\ corporation.\ All\ Microsoft\ Micr$ other product names and logos mentioned herein may be trademarks of their respective companies. Thunderbolt is a trademark of Intel Corporation or its subsidiaries. USB Type-C° and USB-C° are registered trademark of USB Implementers Forum. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. Feature and specification are subject to change without notice. All trademarks and registered trademarks are the property of their respective. All rights reserved.





